

# Sealed ER Rigid Tap Collets - DIN

## Features

Special design locks tap flats into the collet slots preventing the tap from spinning inside the collet.

- DIN Shank and Square Standard
- Sealed by design for high pressure coolant



### Note:

Due to Multiple Standards for Metric Taps, the actual shank and square must be supplied to verify compatibility.



øShank	Inch	Square	Inch	TER16D	TER20D	TER25D	TER32D	TER40D
3.5	0.138	2.7	0.106	TER16D-035-S		TER25D-035-S		
4.0	0.157	3.0	0.118	TER16D-040-S	TER20D-040-S	TER25D-040-S		
4.5	0.177	3.4	0.134	TER16D-045-S	TER20D-045-S	TER25D-045-S	TER32D-045-S	
5.5	0.217	4.3	0.169	TER16D-055-S	TER20D-055-S	TER25D-055-S	TER32D-055-S	
6.0	0.236	4.9	0.193	TER16D-060-S	TER20D-060-S	TER25D-060-S	TER32D-060-S	TER40D-060-S
7.0	0.276	5.5	0.217	TER16D-070-S	TER20D-070-S	TER25D-070-S	TER32D-070-S	TER40D-070-S
8.0	0.315	6.2	0.244	TER16D-080-S	TER20D-080-S	TER25D-080-S	TER32D-080-S	TER40D-080-S
9.0	0.354	7.0	0.276	TER16D-090-S	TER20D-090-S	TER25D-090-S	TER32D-090-S	TER40D-090-S
10.0	0.394	8.0	0.315	TER16D-100-S	TER20D-100-S	TER25D-100-S	TER32D-100-S	TER40D-100-S
11.0	0.433	9.0	0.354			TER25D-110-S	TER32D-110-S	TER40D-110-S
12.0	0.472	9.0	0.354			TER25D-120-S	TER32D-120-S	TER40D-120-S
14.0	0.551	11.0	0.433			TER25D-140-S	TER32D-140-S	TER40D-140-S
16.0	0.630	12.0	0.472			TER25D-160-S	TER32D-160-S	TER40D-160-S
18.0	0.709	14.5	0.571				TER32D-180-S	TER40D-180-S
20.0	0.787	16.0	0.630				TER32D-200-S	TER40D-200-S
22.0	0.866	18.0	0.709					TER40D-220-S

CAT40

CAT50

BT30

BT40

HSK 40E

HSK 63A

HSK 100A

STRAIGHT SHANKS

COLLETS

PARTS & ACCESS.

SHRINK MACHINES

INDEXERS

