

## VU

### TIAN Coated Taps HSS-P - DIN Lengths

Low Carbon Steels <b>33-65</b> SFM	Med Carbon Steels <b>33-98</b> SFM	High Carbon Steels <b>33-98</b> SFM	Alloy Steels <b>33-65</b> SFM
Stainless Steels <b>10-33</b> SFM	Tool Steels <b>16-33</b> SFM	Ductile Cast Irons <b>33-98</b> SFM	
Wrought Aluminum <b>33-98</b> SFM	Aluminum Alloy Cast <b>33-98</b> SFM		

### Features

- Longer Life—Improved tool life from using a high grade of powder high speed steel with a TIAN coating
- Flute Shape—Improved chip evacuation and cutting resistance from a unique flute shape to produce excellent internal threads!
- Total Length—Utilizing a longer overall length to avoid the chips interfering with the holder!
- The Z-PRO VUSP is designed for use with water-soluble tapping fluid where there is a good coolant supply.



## GV

### TIN Coated Taps HSS - ANSI Lengths

Low Carbon Steels <b>15-35</b> SFM	Med Carbon Steels <b>15-35</b> SFM	High Carbon Steels <b>15-35</b> SFM	Alloy Steels <b>15-35</b> SFM
Stainless Steels <b>1-15</b> SFM			
Aluminum Alloy Cast <b>15-65</b> SFM	Zinc Alloy Cast <b>15-65</b> SFM		

### Features

- Custom blended vanadium high speed steel taps with TiN coating achieve longer tool life and stable tapping process
- Optimum cutting edge design specially engineered for highly accurate pitch diameter tolerance and excellent thread surface



### Precision Engineered. Globally Stocked.

Built in Japan using premium Japanese materials, **Yamawa** delivers industry-leading performance at a competitive price. With dedicated inventory in **Chicago** and **Japan**, the tools you need are always within reach.

Contact your local representative at the address below. Let us demonstrate the superior quality and performance of **Yamawa Threading Products**.



### PIONEER N.A. Premium Tool & Work Holding

641 Fargo Ave., Elk Grove Village, IL 60007  
sales@PioneerNA.com | 847-593-6000  
www.PioneerNA.com